

DESCRIPTION:

Our GS series of certified vacuum pumps are A2L compatible. These can handle a wide range of systems with a choice of a 3, 5, 10 and 18 CFM capability.



FEATURES:

- Sparkless DC motor suitable for most refrigerants
- Lightweight and Versatile design
- Dual Stage Reliability



SPECIFICATIONS:

Item No:	GS-3VP	GS-5VP	GS-10VP	GS-18VP
Power:	110V 60Hz	110V 60Hz	110V 60Hz	110V 60Hz
Flow Rate:	3.0 CFM	5.3 CFM	10.2 CFM	18 CFM
# of Stages:	Dual Stage	Dual Stage	Dual Stage	Dual Stage
Horsepower:	1/4 HP	1/4 HP	1 HP	1 HP
Ultimate Vac:	15 Microns	15 Microns	15 Microns	15 Microns
Inlet Port:	1/4 SAE fittings	1/4" & 3/8" SAE	1/4" & 3/8" SAE	1/4", 5/16", 3/8" SAE
Oil Capacity:	8.13 oz	24.4 oz	21.1 oz	38.7 oz
Dimension LxWxH inches	8.5 x 4.1 x 7.9	11.4 x 5 x 10.9	13.7 x 5.5 x 13.1	16 x 6.3 x 13.1
Weight:	7.7 lbs.	11.7 lbs.	24.3 lbs.	31.3 lbs.

Form D-533